

REV. Status

REVISION -
09/08/99 TS

REVISION A
ADDED
TOLERANCES
TO DIMENSIONS
09/28/99 TS

REVISION B
CHANGED
SAFETY TO
UL1950
07/13/00 TS

TELECOMMUNICATION WET COUPLING TRANSFORMER DESIGNED TO OPERATE FROM -20DBm TO +4DBm WITH 0 TO 100mADC IN PRIMARY AND REFLECT A PRIMARY SOURCE IMPEDANCE OF APPROX. 600Ω WITH 470Ω TO 600Ω LOAD ON SECONDARY:


A. Electrical Specifications (@ 25 ° C)

1. Pri Source Impedance; 600Ω
2. Sec Load Impedance; 470Ω
3. Operating Level; -20dBm to +4dBm
4. Insertion Loss;
2.5dB MAX @ 1KHz, 0dBm, DC 30mA
5. Frequency Response (relative to 1 KHz)
±4.0dB 300Hz to 600Hz @ 0dBm
±1.0dB 600Hz to 3.5KHz @ 0dBm
6. Longitudinal Balance;
60dB MIN @ 60Hz to 1KHz
46dB MIN @ 1KHz to 4KHz
7. DC Resistance;
(1-2)= 108Ω +10%, -20%
(3-4)= 120Ω ±10 %
8. Turns Ratio; (1-2):(4-3) = 1:1.00±2%
9. Dielectric Strength;
4000Vrms 1 second Pri to Sec
10. Total Harmonic Distortion:
0.5% MAX @ 300Hz to 3.5KHz, 0dBm, DC0mA



B. Marking; TTC-264M, TAMURA, date code and country of origin

C. Safety: UL1950 Third Edition, File No. E208555

D. Schematic Diagram



E. Mechanical Specifications



MODEL NUMBER

TTC-264M

Discontinued

PREPARED BY:

Dawn Rundle

ENGINEER:

J. Strigman

QUALITY CONTROL:

Don Kelly

Don Kelly

DWG CONTROL NO.
P-A1-12228
ACAD\TTC\A1122281.DWG

REV
B

TELECOMMUNICATION COUPLING
TRANSFORMER

TAMURA CORPORATION OF AMERICA
43352 BUSINESS PARK DRIVE, TEMECULA, CA. 92590-6624
(909) 699-1270 FAX 9096769482

TTC-264M

MODEL SPECIFICATION

DIM: mm(ln) SCL: 1/1 SH: 1 OF 1

PROPRIETARY NOTICE: THIS DRAWING PRINT OR DOCUMENT AND SUBJECT MATTER DISCLOSED HEREIN ARE PROPRIETARY ITEMS TO WHICH TAMURA RETAINS THE EXCLUSIVE RIGHT OF DISSEMINATION, REPRODUCTION, MANUFACTURE AND SALE. THIS DRAWING, PRINT OR DOCUMENT IS SUBMITTED IN CONFIDENCE FOR CONSIDERATION BY THE RECIPIENT ALONE UNLESS PERMISSION FOR FURTHER DISCLOSURE IS EXPRESSLY GRANTED IN WRITING.